

# AC axial fan - HyBlade

sickle-shaped blades (S series)

with guard grille for short nozzle

## ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.ebmpapst.com

www.ebmpapst.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

|                             |                   |      |      |
|-----------------------------|-------------------|------|------|
| Type                        | S4E500-AM03-01    |      |      |
| Motor                       | M4E110-GF         |      |      |
| Phase                       |                   | 1~   | 1~   |
| Nominal voltage             | VAC               | 230  | 230  |
| Frequency                   | Hz                | 50   | 60   |
| Method of obtaining data    |                   | ml   | ml   |
| Valid for approval/standard |                   | CE   | CE   |
| Speed (rpm)                 | min <sup>-1</sup> | 1300 | 1400 |
| Power consumption           | W                 | 680  | 880  |
| Current draw                | A                 | 3.0  | 3.88 |
| Capacitor                   | µF                | 12   | 12   |
| Capacitor voltage           | VDB               | 450  | 450  |
| Max. back pressure          | Pa                | 150  | 100  |
| Max. back pressure          | in. wg            | 0.6  | 0.4  |
| Min. ambient temperature    | °C                | -40  | -40  |
| Max. ambient temperature    | °C                | 65   | 40   |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

## Data according to Commission Regulation (EU) 327/2011

|                                   |   | Actual | Req. 2015 |
|-----------------------------------|---|--------|-----------|
| 01 Overall efficiency $\eta_{es}$ | % | 32.5   | 32.5      |
| 02 Measurement category           |   | A      |           |
| 03 Efficiency category            |   | Static |           |
| 04 Efficiency grade N             |   | 40     | 40        |
| 05 Variable speed drive           |   | No     |           |

Data obtained at optimum efficiency level.

The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

|                               |                   |      |
|-------------------------------|-------------------|------|
| 09 Power consumption $P_e$    | kW                | 0.65 |
| 09 Air flow $q_v$             | m³/h              | 5765 |
| 09 Pressure increase $p_{fs}$ | Pa                | 129  |
| 10 Speed (rpm) n              | min <sup>-1</sup> | 1315 |
| 11 Specific ratio*            |                   | 1.00 |

\* Specific ratio =  $1 + p_{fs} / 100\,000\text{ Pa}$

LU-107128



# AC axial fan - HyBlade

sickle-shaped blades (S series)

with guard grille for short nozzle

## Technical description


|                                                                            |                                                                    |
|----------------------------------------------------------------------------|--------------------------------------------------------------------|
| Size                                                                       | 500 mm                                                             |
| Motor size                                                                 | 110                                                                |
| Rotor surface                                                              | Painted black                                                      |
| Terminal box material                                                      | PC/ABS plastic, black                                              |
| Blade material                                                             | Press-fitted sheet steel blank, sprayed with PP plastic            |
| Guard grille material                                                      | Steel, phosphated and coated with black plastic                    |
| Number of blades                                                           | 5                                                                  |
| Airflow direction                                                          | V                                                                  |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                              |
| Degree of protection                                                       | IP54                                                               |
| Insulation class                                                           | "F"                                                                |
| Moisture (F) / Environmental (H) protection class                          | F4-1                                                               |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                            |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                            |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request       |
| Condensation drainage holes                                                | On rotor side                                                      |
| Mode                                                                       | S1                                                                 |
| Motor mounting                                                             | Ball bearing                                                       |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 3.5 mA                                                          |
| Electrical hookup                                                          | Terminal box; Via terminal box, capacitor integrated and connected |
| Motor protection                                                           | Thermal overload protector (TOP) with basic insulation             |
| With cable                                                                 | Axial                                                              |
| Protection class                                                           | I (with customer connection of protective earth)                   |
| Motor capacitor according to EN 60252-1 in safety protection class         | S0                                                                 |
| Conformity with standards                                                  | EN 61800-5-1; CE                                                   |
| Approval                                                                   | CCC; EAC; VDE; UL 1004-1; CSA C22.2 No. 100                        |



# AC axial fan - HyBlade

sickle-shaped blades (S series)  
with guard grille for short nozzle

## Product drawing




|   |                                                                          |
|---|--------------------------------------------------------------------------|
| 1 | Direction of air flow "V"                                                |
| 2 | Tightening torque $0.8 \pm 0.15$ Nm                                      |
| 3 | Cable diameter min. 6 mm, max. 12 mm, tightening torque $2.0 \pm 0.3$ Nm |

# AC axial fan - HyBlade

sickle-shaped blades (S series)  
with guard grille for short nozzle

## Connection diagram




|    |              |     |       |   |              |
|----|--------------|-----|-------|---|--------------|
| L  | = U1 = blue  | Z   | brown | N | = U2 = black |
| PE | green/yellow | TOP | gray  |   |              |



# AC axial fan - HyBlade

sickle-shaped blades (S series)  
with guard grille for short nozzle

## Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-107128-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | LwA <sub>out</sub> | q <sub>v</sub>    | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|-------------------|-------------------|--------------------|-------------------|-----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | dB(A)             | dB(A)             | dB(A)              | m <sup>3</sup> /h | Pa              | cfm            | in. wg          |
| 1 | 230 | 50 | 1380              | 513            | 2.25 | 68                | 75                | 75                 | 8905              | 0               | 5240           | 0.00            |
| 2 | 230 | 50 | 1355              | 572            | 2.51 | 65                | 72                | 72                 | 7900              | 50              | 4650           | 0.20            |
| 3 | 230 | 50 | 1330              | 626            | 2.74 | 63                | 70                | 70                 | 6610              | 100             | 3890           | 0.40            |
| 4 | 230 | 50 | 1300              | 680            | 3.00 | 66                | 73                | 73                 | 4930              | 150             | 2900           | 0.60            |


U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
LwA<sub>out</sub> = Sound power level outlet side · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase



# AC axial fan - HyBlade

sickle-shaped blades (S series)  
with guard grille for short nozzle

## Curves: Air performance 60 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-107130-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | LwA <sub>out</sub> | q <sub>v</sub>    | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|-------------------|-------------------|--------------------|-------------------|-----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | dB(A)             | dB(A)             | dB(A)              | m <sup>3</sup> /h | Pa              | cfm            | in. wg          |
| 1 | 230 | 60 | 1530              | 793            | 3.45 | 70                | 77                | 78                 | 9850              | 0               | 5800           | 0.00            |
| 2 | 230 | 60 | 1485              | 830            | 3.62 | 68                | 75                | 75                 | 8945              | 40              | 5265           | 0.16            |
| 3 | 230 | 60 | 1445              | 854            | 3.74 | 66                | 73                | 73                 | 8170              | 70              | 4810           | 0.28            |
| 4 | 230 | 60 | 1400              | 880            | 3.88 | 65                | 71                | 71                 | 7240              | 100             | 4260           | 0.40            |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
LwA<sub>out</sub> = Sound power level outlet side · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

